



# ATLANTIDA COLLECTION

CONTRACT • AUTOMOTIVE • UPHOLSTERY

*Natural Leather*

## TECHNICAL DATASHEET

	TEST METHOD PRÜFVERFAHREN METHOD TEST MÉTODO DE PRUEBA	MEASUREMENT UNIT MAßEINHEIT UNIT OF MEASUREMENT UNIDAD DE MEDIDA	GUARANTEED GARANTIERT INSURED GARANTIZADA
<b>BURNING BEHAVIOUR TO CIGARETTE AND MATCH FLAME</b> BRANDVERHALTEN GGÜ. ZIGARETTENGLUT UND STREICHHOLZFLAMME COMPORTEMENT DE COMBUSTION DES CIGARETTES ET ALLUMETTES COMPORTAMIENTO FRENTE AL FUEGO Y LLAMA	CAL TB-117 (2013, Sec.1) BS 5852:1979 BS EN 1021-1-2:2006	IMO RES A652(16) FIRE RETARDANT	PASS
<b>COLOUR FASTNESS TO RUBBING   DRY 500 CYCLES</b> ABRIEBFESTIGKEIT   TROCKEN 500 ZYKLEN RÉSISTANCE AUX FROTTEMENTS   A SEC 500 CYCLES SOLIDEZ DEL COLOR AL FROTE   A SECO 500 CICLOS	UNI EN ISO 11640:1998	GREY SCALE	≥ 4
<b>COLOUR FASTNESS TO RUBBING   WET 250 CYCLES</b> ABRIEBFESTIGKEIT   NASS 250 ZYKLEN RÉSISTANCE AUX FROTTEMENTS   HUMIDE 250 CYCLES SOLIDEZ DEL COLOR AL FROTE   MOJADO 250 CICLOS	UNI EN ISO 11640:1998	GREY SCALE	≥ 4
<b>COLOUR FASTNESS TO RUBBING   SWEAT 80 CYCLES</b> ABRIEBFESTIGKEIT   SCHWEIß 80 ZYKLEN RÉSISTANCE AUX FROTTEMENTS   SUEUR 80 CYCLES SOLIDEZ DEL COLOR AL FROTE   SUDOR 80 CICLOS	UNI EN ISO 11640:1998 ISO 11641 pH8	GREY SCALE	≥ 4
<b>FLEXING ENDURANCE   DRY 50.000 CYCLES</b> BIEGEFESTIGKEIT   TROCKEN 50.000 ZYKLEN RÉSISTANCE À LA FLEXION   A SEC 50.000 CYCLES RESISTENCIA A LA FLEXIÓN   A SECO 50.000 CICLOS	UNI EN ISO 5402		NO DAMAGE
<b>FINISH ADHESION   DRY</b> HAFTUNG DER OBERFLÄCHENBEHANDLUNG   TROCKEN ADHÉSION DU FILM   A SEC ADHERENCIA DE ACABADO   A SECO	UNI EN ISO 11644	N/cm	≥ 2
<b>TEAR STRENGTH   SINGLE EDGE TEAR</b> REIßFESTIGKEIT HOSE   EINKANTENRISS RÉSISTANCE AU DÉCHIREMENT   BORD UNIQUE RESISTENCIA AL DESGARRO   DESGARRO SIMPLE	UNI EN ISO 3377-1	N	≥ 20
<b>COLOUR FASTNESS TO ARTIFICIAL LIGHT   EXPOSITION ENERGY 16.000 kj/sqm</b> UV-BESTÄNDIGKEIT   EXPOSITIONS ENERGIE 16.000 kj/qm RÉSISTANCE À LA LUMIÈRE ARTIFICIELLE   ÉNERGIE D'EXPOSITION 16.000 kj/m <sup>2</sup> SOLIDEZ DEL COLOR A LA LUZ ARTIFICIAL   EXPOSICIÓN A ENERGÍA 16.000 kj/m <sup>2</sup>	UNI EN ISO 105 B02 (MET.5)	BLUE SCALE	≥ 5

## CLEAN AND CARE RECOMMENDATIONS

EUROPEAN BOVINE ORIGIN, LIGHTLY BUFFED NATURAL GRAIN  
PROTECTIVE TOP COAT, SOFT WAXY FEEL, SEMI-MATTE FINISH  
1.2 - 1.4 mm THICKNESS | 4.8 - 5.0 sqm AVERAGE

TO REMOVE DUST USE A VACUUM CLEANER.

AVOID EXPOSING DIRECTLY TO SUNLIGHT AND HEAT SOURCES.

ANY STAIN, SPILLS OR SOILING SHOULD BE CLEANED UP PROMPTLY WITH A NEUTRAL SOAP SOLUTION USING A CLOTH IN SMOOTH CIRCULAR MOVEMENTS.

WE DO NOT ACCEPT RESPONSIBILITY FOR ANY DAMAGE RESULTING FROM INAPPROPRIATE USE, CHEMICAL CLEANING OR ADDITIONAL IMPREGNATION.

## DELIVERY AND SHIPPING

4/5 DAYS DELIVERY TIME

EXPRESS SERVICE - READY TO SHIP IN 48h

WORLDWIDE SHIPPING AVAILABLE

\* All colours available from European origin (with IMO RES A652(16))

HOTCOLOURS - optional version from Brazilian or Extra EU origin